

Fully Automatic 'Hollowrap' Slitter Rewinder

Specification

- ❑ Maximum parent roll width 20" (500mm)
- ❑ Maximum parent roll diameter 20" (500mm)
- ❑ Accepts parent rolls on 3" (76mm) I.D. cores.
- ❑ Master roll lifting table.
- ❑ Six adjustable slitting blades
- ❑ Interchangeable steering units for 3", 5" and 10" web widths.
- ❑ Full width rewinding capability.
- ❑ Adjustable external electronic rewind tension from -3% to +5% in increments of 0.1%
- ❑ Variable speed drives giving a machine capability of up to 3000' (1000 m) per minute.
- ❑ Programmable electronic length counter.
- ❑ HMI control panel.
- ❑ Film break sensors
- ❑ Patented Hollowrap™ Rewind Mandrels
- ❑ Automatic single twin turret rewind arm.
- ❑ Automatic film attachment.
- ❑ Automatic film cut off.
- ❑ Automatic finished roll unloading
- ❑ Rewind roll maximum diameter 8.5" (220mm)
- ❑ Finished roll return exit conveyor.
- ❑ 3 - phase 220-400 volt 50-60Hz supply. / Air requirements - 4 cfm max. at 80 psi.



CG Automatic Converting Equipment Ltd

8 Highmeres Rd
Leicester LE4 9LZ
England

Ph +44 116 2760206 Fax +44 116 2742995

Designing, Manufacturing & Supplying

Slitting, Rewinding, Coreless rewinding, Prestretch, Perforators &
Special Purpose Machines.

sales@cga-converting.com / www.cga-converting.com